



Model :	BSC-18
Voltage :	220V/50HZ/1 Phase
Power :	1.8 KW
Capacity (Liters/Hr) :	18
Dimension (mm) (NET) :	440/700/735
Dimension (mm) (PACKING) :	515/775/900
N. W. (Kg) :	100
G. W. (Kg) :	110



Model :	BSC-20
Voltage :	220V/50HZ/1 Phase
Power :	2.3 KW
Capacity (Liters/Hr) :	20
Dimension (mm) (NET) :	550/650/960
Dimension (mm) (PACKING) :	650/780/1160
N. W. (Kg) :	140
G. W. (Kg) :	160



Model :	BSC-25 / BSC-25A
Voltage :	220V/50HZ/1 Phase
Power :	2.4 KW
Capacity (Liters/Hr) :	25
Dimension (mm) (NET) :	550/650/960
Dimension (mm) (PACKING) :	650/780/1160
N. W. (Kg) :	BSC-25 : 150 / BSC-25A : 160
G. W. (Kg) :	BSC-25 : 170 / BSC-25A : 180



Model :	BSF-40 / BSF-40A
Voltage :	220V/50HZ/1 Phase
Power :	2.7 KW
Capacity (Liters/Hr) :	40
Dimension (mm) (NET) :	550/650/1340
Dimension (mm) (PACKING) :	650/780/1520
N. W. (Kg) :	BSF-40 : 190 / BSF-40A : 200
G. W. (Kg) :	BSF-40 : 210 / BSF-40A : 220



Model :	BSF-40AP3
Voltage :	380-450V/50HZ/3 Phase
Power :	4.0 KW
Capacity (Liters/Hr) :	40
Dimension (mm) (NET) :	550/650/1540
Dimension (mm) (PACKING) :	650/780/1750
N. W. (Kg) :	180
G. W. (Kg) :	200



Model :	BSF-50
Voltage :	220V/50HZ/1 Phase
Power :	3.5 KW
Capacity (Liters/Hr) :	50
Dimension (mm) (NET) :	550/650/1340
Dimension (mm) (PACKING) :	650/780/1520
N. W. (Kg) :	210
G. W. (Kg) :	230



Model :	BSF-50P3 / BSF-50AP3
Voltage :	380-450V/50HZ/3 Phase
Power :	3.3 KW
Capacity (Liters/Hr) :	50
Dimension (mm) (NET) :	550/650/1340
Dimension (mm) (PACKING) :	650/780/1520
N. W. (Kg) :	BSF-50P3 : 180 / BSF-50AP3 : 240
G. W. (Kg) :	BSF-50P3 : 200 / BSF-50AP3 : 210



Model :	BSF-60P3 / BSF-60AP3
Voltage :	380-450V/50HZ/3 Phase
Power :	5.4 KW
Capacity (Liters/Hr) :	60
Dimension (mm) (NET) :	600/700/1540
Dimension (mm) (PACKING) :	650/780/1160
N. W. (Kg) :	BSF-60P3 : 180 / BSF-60AP3 : 240
G. W. (Kg) :	BSF-60P3 : 250 / BSF-60AP3 : 260